






T I L E P A N E L

INSULATED PANEL SYSTEMS FOR CONSTRUCTION
TOPCOVER TILE / TOPCOVER TILE MARSELHA



O FELIZ
PAINEL



Description/Application

Panel with the shape of a traditional tile for roofs with a minimum slope of 10%.
Insulating product composed of two profiled metal sheets, joined by an insulating core made of rigid polyurethane (PUR) or polyisocyanurate (PIR) foam. The exterior panel has a textured paint finish for a greater resemblance to traditional tiles.
In harsher environments, it is recommended to apply silicone to the panel joint to prevent condensation.

Characteristics

Dimensions*

Thicknesses: 30-40-50 mm ± 2 mm
Width: 1000 mm ± 2 mm
Length: 2,10 – 14,00 m, in multiples of 0,35 m
Maximum recommended length: 8,05 m

Metallic support

Steel grade S250GD, EN 10346
Thicknesses: 0,4-0,5-0,6 mm

Insulated core

Polyurethane (PUR) | Polyisocyanurate (PIR)

Thermal conductivity:

PUR 0,0207 W/m $^{\circ}$ C

PIR 0,0207 W/m $^{\circ}$ C

Density: 40 kg/m³

Reaction to fire:

PUR B-s2,d0

PIR B-s2,d0

PIR-HI B-s1,d0

Coating


Standard: Polyester paint texturada 25 μ m.

Special: Granite HDX 55 μ m | Naive Wood textured color for the interior.

Option for metallic coating in lacquered aluminum.

*Tolerances according to EN 14509

W/m K = W/m $^{\circ}$ C | W/m² K = W/m² $^{\circ}$ C



Description/Application

Panel with the shape of a traditional tile for roofs with a minimum slope of 10%.
Insulating product composed of two profiled metal sheets, joined by an insulating core made of rigid polyurethane (PUR) or polyisocyanurate (PIR) foam.
The exterior panel has a textured paint finish for a greater resemblance to traditional tiles.
In harsher environments, it is recommended to apply silicone to the panel joint to prevent condensation.

Characteristics

Dimensions*

Thicknesses: 40–60–80 mm ± 2 mm
Width: 1000 mm ± 2 mm
Length: 2,10 – 14,00 m, in multiples of 0,35 m
Maximum recommended length: 8,05 m

Metallic support

Steel grade S250GD, EN 10346
Thicknesses: 0,4–0,5–0,6 mm

Insulated core

Polyurethane (PUR) | Polyisocyanurate (PIR)

Thermal conductivity:

PUR 0,0207 W/m °C

PIR 0,0207 W/m °C

Density: 40 kg/m³

Reaction to fire:

PUR B-s2,d0

PIR B-s2,d0

PIR-HI B-s1,d0

Coating

Standard: Polyester paint texturada 25 μ m.

Special: Granite HDX 55 μ m | Naive Wood textured color for the interior.

Option for metallic coating in lacquered aluminum.

*Tolerances according to EN 14509

W/m K = W/m °C | W/m² K = W/m² °C

Topcover Tile color range

All RAL references presented here have a textured finish.

Exterior side


RAL 8004T Copper brown



RAL 8023T Orange brown



RAL 9005T Jet black



Interior side

RAL 9010 Pure white



Naive Wood Textured lacquer



Alvero



Patinao Spanish roof



Headquarters

Av. de São Lourenço, N° 41
4705-444 Celeirós, Braga
Portugal

T +351 253 305 600
info@ofelizpainel.com
ofelizpainel.com

Factory/Sales Dep.

Av. de São Pedro, N° 22
4705-630 Tebosa, Braga
Portugal

T +351 253 776 600